

Pole cover with flap. L= 2400mm**PHOTOS**

Dimensions: (2400x250) mm
Weight: 970 g

Length and weight tolerances are $\pm 2\%$. Due to continuous product development, product appearance may differ slightly from that shown in the photos.

CHARACTERISTICS

The cover is made of polyester fabric coated with a water-resistant PVC layer. The cover fastens with Velcro straps. The cover includes internal pockets for organizing and transporting the poles.

APPLICATION

The cover is designed for proper protection, transport, storage and sorting of rod segments.

STORAGE AND MAINTENANCE

The cover should be stored in a manner that protects it from mechanical damage. Store the cover in a dry place, away from heat sources, in a chemically non-aggressive atmosphere. Protect from sunlight. To clean, use a cloth dampened with water and a mild detergent. Dry at a temperature not exceeding 50°C.

EXAMINATION

Before placing the pole segments in their case, remove any dirt. Periodic inspections should be performed annually.

Pole cover with flap. L= 2400mm

The visual inspection includes checking:

- the exterior and interior surfaces of the cover (the surfaces should be clean, free of abrasions or other visible defects),
- the transport handle.

A damaged, heavily worn, or dirty cover should not be used to transport telescopic poles. If the cover becomes damp (especially on the interior surface), dry it thoroughly before inserting the pole segments.

FREQUENCY TESTS

For check and periodic inspection to be carried out in according to table.

	CHECK	PERIODIC INSPECITON
Who	Team Leader / Foreman	Supervision
When	Before each use	Once a year*
How	Visually (visual inspection)	Visually (visual inspection)

*Unless instructions say otherwise